



CARL ROBINSON

Industrial meets modern in Carl Robinson's new contract collection. Untraditional luxury is displayed throughout this collection with a wide variety of textured type II vinyl wallcoverings. Sophisticated and bold patterns are artfully paired with metallics and new embosses. Refined experimental designs inspired by both nature and industry create an avant-garde collection with a masculine touch. This collection includes type II vinyl wallcoverings that are available for both commercial and residential spaces, as shown in the Robinson's 17th edition LOFT.





CARL ROBINSON





CARL ROBINSON

QUEENSGATE





## QUEENSGATE

52"-54" Type II 20 oz. Contract Wallcovering



SNOW

CR86710



WHEAT

CR86705



ABALONE

CR86707



CEDAR

CR86706



STONE

CR86708



DENIM

CR86702

PHYSICAL PROPERTIES	
Unit Weight	20.0 oz. per square yard
Backing	Non-woven
Width	52"-54"

All patterns are shown in 20" square panels.

DESIGN INFORMATION	
Match	Random / Breakable
Repeat	Random

FEDERAL SPECIFICATIONS	
General	ASTM D1557 (Type II)
Performance	ASTM D1557 (Type II)
Fire Hazard	ASTM E84 (Type II)

ASTM D1557 (Type II) is the standard for Type II wallcoverings.

**ANTIBACTERIAL FEATURES**  
This wallcovering contains bacteriostatic and bactericidal additives to discourage the growth of bacteria and mold under normal conditions.

**STAIN RESISTANCE**  
This wallcovering is resistant to staining and discoloration.

**WEAR RESISTANCE**  
This wallcovering is resistant to wear and tear.

FIRE HAZARD CLASSIFICATION RESULTS	
Smoke Density	ASTM E84 (Type II)
Flame Spread	ASTM E84 (Type II)

The product is intended for use in buildings that are properly designed and constructed to meet smoke, fire, and life safety requirements.

**COPYRIGHT**  
Copyright © 2021 Carl Robinson. All Rights Reserved.  
WALLCOVERING, Inc. 4400 Queen Road Drive, Memphis, TN 38117 USA  
(866) 425-0255 | [carl@wallcovering.com](mailto:carl@wallcovering.com) | [www.wallcovering.com](http://www.wallcovering.com)



CARL ROBINSON

QUEENSDOWN





CARL ROBINSON

QUEENSDOWN | MERCURY | CR86208



## QUEENSDOWN

52" x 54" Type II 20 oz. Contract Wallcovering



QUARTZ

CR86210



FLAX

CR86215



TITANIUM

CR86228




STONE

CR86207



CABRETTA

CR86217



SLATE

CR86218



AGATE

CR86205



HICKORY

CR86216



CRIMSON

CR86201



COPPER

CR86206



CHARCOAL

CR86200



COBALT

CR86202

### PHYSICAL PROPERTIES

Unit Weight: 20.0 lbs per square yard  
Backing: 52" x 54"  
Moisture: 100% relative humidity

### DESIGN INFORMATION

Match: Random / Repeatable  
Repeat: Random

### FEDERAL SPECIFICATIONS

Complies with U.S. Federal Specification (22 CFR 161.10) for Type II materials used for protection against fire and explosion (22 CFR 161.10). The wallcovering meets the Federal Fire Protection Association (FFPA) Class A Fire Test.

### ANTIBACTERIAL FEATURES

Wallcovering contains bactericides and mold inhibitors to discourage the growth of mold and mildew under normal conditions.

### SEVEN YEAR WARRANTY AGAINST MANUFACTURING DEFECTS

See only wallcovering and printed on manufacturer's label for warranty details.

### FIRE HAZARD CLASSIFICATION RESULTS

• TESTED IN ACCORDANCE WITH ASTM E 84 (TUNING TEST)  
• CLASS "0" (FIRE RESISTANT) • CLASS "0" (FIRE RESISTANT)  
• CLASS "0" (FIRE RESISTANT) • CLASS "0" (FIRE RESISTANT)

The product is intended for use in buildings that are properly designed and constructed to resist smoke, fire, and explosion under normal conditions of use.

### COPYRIGHT

Copyright © 2021 Carl Robinson. All Rights Reserved.  
WALLCOVERING, Inc. 4400 Queen Road Drive, Memphis, TN 38117 USA  
(800) 425-0255 | [carl@wallcovering.com](mailto:carl@wallcovering.com) | [www.wallcovering.com](http://www.wallcovering.com)



CARL ROBINSON

QUEENSCROFT





CARL ROBINSON

QUEENSCROFT | CAYMAN BLUE | CR85822



## QUEENSCROFT

52"-54" Type II 20 oz. Contract Wallcovering



POLAR CR85810



COTTAGE CR85807



QUIET VISTA CR85802



MALT CR85805



SHEA BUTTER CR85825



JUNIPER BERRY CR85812



SWISS COFFEE CR85815



COOL WIND CR85808



THAI BASIL CR85804



TILE CR85806



SANDY COAST CR85818



THISTLE STEM CR85800



BUCKWHEAT CR85803



BERING BLUE CR85828



WINE CR85809



CARDINAL CR85801

**PHYSICAL PROPERTIES**  
U.S. UNITS  
Total Weight 20.0 oz. per square yard  
Backing Nonwoven  
Width 52"-54"  
METRIC UNITS  
450 grams per square meter  
Nonwoven  
1334 - 1357mm

All patterns are shown as a 20" heavy grid cloth.

**DESIGN INFORMATION**  
Match Random / Directional  
Repeat Random

**FEDERAL SPECIFICATIONS**  
Complies with U.S. Federal Specification GCS-10400 for Type II materials using the procedure detailed in Federal Specification GCS-10400. The wallcovering meets the Federal Test Procedure Association (FTP) 208.1-Cover Test.

**ANTIBACTERIAL FEATURES**  
Wall covering contains bactericides and mildew inhibitors to discourage the growth of mold and mildew under normal conditions.

**SEVEN YEAR WARRANTY AGAINST MANUFACTURING DEFECTS**  
See only wallcovering and printed on manufacturer's label for warranty.

**FIRE HAZARD CLASSIFICATION RESULTS**  
• TESTED IN ACCORDANCE WITH ASTM E 84 (TUNNEL TEST)  
• CLASS "0" FRI (SMALL)  
• CLASS "0" FRI (SMALL)  
• CLASS "0" FRI (SMALL)  
• CLASS "0" FRI (SMALL)  
The product is intended for use in buildings that are properly designed and constructed to resist smoke, fire, and toxic gases, and is not intended for use in areas where fire, smoke, or toxic gases are likely to occur.  
**COPYRIGHT**  
Copyright © 2021 Carl Robinson. All Rights Reserved.  
WALLCOVERING INC. 4401 Queen Road Drive, Memphis, TN 38117 USA  
(866) 425-0255 | [carl@wallcovering.com](mailto:carl@wallcovering.com) | [www.wallcovering.com](http://www.wallcovering.com)





CARL ROBINSON

QUEENSMILL



CARL ROBINSON

QUEENSMILL | SLATE | CR87518



## QUEENSMILL

52"-54" Type II 20 oz. Contract Wallcovering



PARMESAN

CR87505



BISCOTTI

CR87507



STONE

CR87508

### PHYSICAL PROPERTIES

Line Weight	U.S. 20.0 lbs	METRIC 9.085
	20.0 grams per linear yard	6.76 grams per linear meter
Backing	0.3 oz per square yard	45.5 grams per square meter
Width	52"-54"	1.334 - 1.37m

All patterns are shown as a 20" linear yard.

### DESIGN INFORMATION

Match	Design	Design
Repeat	20"	30.0m

### FEDERAL SPECIFICATIONS

Complies with U.S.A. Federal Specification GCS-10438B for Type II materials using the procedure detailed in Federal Specification GCS-10438B. The wallcovering meets the Federal Test Procedure Association (FTPA) 204-Cover Test.

### ANTIBACTERIAL FEATURES

Wall-coverings contain bactericides and mildew inhibitors to discourage the growth of mold and mildew under normal conditions.

### 5-YEAR WARRANTY AGAINST MANUFACTURING DEFECTS

See only references and printed on manufacturer's label for warranty.

### FIRE HAZARD CLASSIFICATION RESULTS

- TESTED IN ACCORDANCE WITH ASTM E 84 (TUNNEL TEST)
- CLASS "0" (FBI 302.53)
- FLSHA (NFPA 704) 0-0-0

The product is intended for use in buildings that are properly designed and constructed to avoid smoke infiltration, smoke damage and/or carbon dioxide at wall openings and wall surfaces, particularly in areas of high fire risk.

### COPYRIGHT

Copyright © 2021 Carl Robinson. All Rights Reserved.  
WALLQUEST INC., 4401 Queen Road Drive, Memphis, TN 38117 USA  
(800) 425-0255 | [carl@wallquest.com](mailto:carl@wallquest.com) | [www.wallquest.com](http://www.wallquest.com)





CARL ROBINSON

QUEENSWAY



CARL ROBINSON

QUEENSWAY | LEISURE | CR87901




## QUEENSWAY

52"-54" Type II 20 oz. Contract Wallcovering



SAND

CR87907



CHARCOAL

CR87908



KHAN

CR87905



CAROB

CR87906



ANCHOR

CR87902

**PHYSICAL PROPERTIES**  
U.S. UNITS  
Total Weight 20.0 lbs per linear yard  
D 3.3 oz per square yard  
Backing None  
Width 52"-54"  
METRIC UNITS  
450 grams per linear meter  
453 grams per square meter  
Nonwoven  
1.33m - 1.37m

All patterns are shown on a 30" linear grid.

**DESIGN INFORMATION**  
Match Straight  
Repeat 20"

**FEDERAL SPECIFICATIONS**  
Complies with U.S. Federal Specification (22) (W-438) for Type II materials using hot glue adhesive. Meets U.S. Federal Specification (22) (W-438). This wallcovering meets the Federal Test Procedure Association (FTPA) 200A Cover Test.

**ANTIBACTERIAL FEATURES**  
This wallcovering contains bactericides and mildew inhibitors to discourage the growth of mold and mildew under normal conditions.

**SEVEN YEAR WARRANTY AGAINST MANUFACTURING DEFECTS**  
See only wallcovering and printed on manufacturer's label for details.

**FIRE HAZARD CLASSIFICATION RESULTS**  
• TESTED BY ACCORDANCE WITH ASTM E 84 (TUNNEL TEST)  
• CLASS "0" FIBERGLASS • TACHO QUALIFIED 20  
• FLAME SKEWED 00 • RY 2000 (B-1-L)

This product is intended for use in buildings that are properly designed and constructed to avoid smoke infiltration, smoke toxicity and/or carbon dioxide at wall openings and wall systems, particularly in areas of high fire risk.

**COPYRIGHT**  
Copyright © 2020 Carl Robinson. All Rights Reserved.  
WALLCOVERING INC., 4400 Queen Road Drive, Memphis, TN 38117 USA  
(800) 425-0255 | [carlrobinson@wallcovering.com](mailto:carlrobinson@wallcovering.com) | [www.wallcovering.com](http://www.wallcovering.com)





CARL ROBINSON

QUEENSWOOD



CARL ROBINSON

QUEENSWOOD | GRAPHITE | CR88008



## QUEENSWOOD

52"-54" Type II 20 oz. Contract Wallcovering



LEISURE

CR88001



ALCHEMY

CR88002



SAND

CR88007



IRON

CR88018



CAROB

CR88006



COFFEE

CR88016



KHAN

CR88005



ANCHOR

CR88012

PHYSICAL PROPERTIES	
U.S. UNITS	METRIC UNITS
Sheet Weight	20.0 lbs per square yard
Backing	45.0 grams per square meter
Width	52" - 54"
	1.334 - 1.250m

All patterns are shown in 30" square panels.

DESIGN INFORMATION	
Match	Random / Breakable
Repeat	Random

FEDERAL SPECIFICATIONS	
General	U.S. Army (U.S. Army) Type II (Type II)
Materials	U.S. Army (U.S. Army) Type II (Type II)
Performance	U.S. Army (U.S. Army) Type II (Type II)

ANCHORING FEATURES  
Wallcovering contains anchor rods and rubber shims to secure the product to the wall.

WEAR WARRANTY AGAINST MANUFACTURING DEFECTS  
See only information and printed on manufacturer's label.

FIRE HAZARD CLASSIFICATION RESULTS	
• TESTED BY ACCORDANCE WITH ASTM E 84 (TUNNEL TEST)	• CLASSIFIED PER NFPA 260
• CLASSIFIED PER NFPA 260	• CLASSIFIED PER NFPA 260

The product is intended for use in buildings that are properly designed and constructed to meet smoke, fire, and sound transmission requirements.

COPYRIGHT  
Copyright © 2021 Carl Robinson. All Rights Reserved.  
WALLCOVERING, 4400 Queen Road Drive, Memphis, TN 38117 USA  
(800) 425-0255 | [carl@wallcovering.com](mailto:carl@wallcovering.com) | [www.wallcovering.com](http://www.wallcovering.com)





CARL ROBINSON

QUEENSBURY



CARL ROBINSON

QUEENSBURY | HAZELNUT | CR85501



## QUEENSBURY

52" x 54" Type II 20 oz. Contract Wallcovering



BUTTERMILK

CR85505



SANDCASTLE

CR85508



FAWN

CR85507



FROST

CR85504

### PHYSICAL PROPERTIES

Line Weight	2.5 LB/SY	WET TENSILE	180 grams per square yard
Backing	20 mil per square yard	Wet Tensile	435 grams per square yard
Width	52" x 54"	Wet Tensile	1.20 in. x 1.20 in.

All patterns are shown in a 20" square patch.

### DESIGN INFORMATION

Match	Random / Repeatable	Random / Repeatable
Repeat	Random	Random

### FEDERAL SPECIFICATIONS

Complies with U.S.A. Federal Specification GCS-1048B for Type II materials using the procedure detailed in Federal Specification GCS-1048B. The wallcovering meets the Federal Test Procedure Association (FTP) 208A Color Fastness Test.

### ANTIBACTERIAL FEATURES

Wallcoverings contain bactericides and mold inhibitors to discourage the growth of mold and mildew under normal conditions.

### SEVEN YEAR WARRANTY AGAINST MANUFACTURING DEFECTS

See only wallcovering and printed on manufacturer's label for details.

### FIRE HAZARD CLASSIFICATION RESULTS

- TESTED IN ACCORDANCE WITH ASTM E 84 (TUNING TEST)
- CLASS "0" (FIRE RESISTANT)
- CLASS "0" (FIRE RESISTANT)
- CLASS "0" (FIRE RESISTANT)

The product is intended for use in buildings that are properly designed and constructed to resist smoke infiltration, smoke toxicity and/or carbon dioxide, at wall, ceiling and wall systems, particularly in areas of high fire risk.

### COPYRIGHT

Copyright © 2021 Carl Robinson. All Rights Reserved.  
WALLCOVERING INC., 4400 Queen Road Drive, Memphis, TN 38117 USA  
(800) 425-0255 | [carl@wallcovering.com](mailto:carl@wallcovering.com) | [www.wallcovering.com](http://www.wallcovering.com)





CARL ROBINSON

QUEENSLAND



## QUEENSLAND

52" x 54" Type II 20 oz. Contract Wallcovering



QUILL GRAY

CR86918



QUICKSILVER

CR86904



FLAX

CR86907



INDEPENDENCE

CR86901

### PHYSICAL PROPERTIES

Unit Weight: 20.0 lbs per square yard  
Backing: Non-woven  
Width: 52" x 54"

WET WEIGHT: 400 grams per square meter  
WET WEIGHT: 400 grams per square meter  
Wet Weight: 1.20 lb - 1.25 lb

### DESIGN INFORMATION

Match: Half Drop  
Repeat: 28.2"

Half Drop  
72.4 in.

### FEDERAL SPECIFICATIONS

Complies with U.S. Federal Specification GCS (W-408) for Type II materials, using the procedure detailed in Federal Specification GCS-1, 19.8. The wallcovering meets the Federal Test Procedure Association (FTP) 260A Color Fastness Test.

### ANTIBACTERIAL FEATURES

Wall-coverings contain bactericides and mildew inhibitors to discourage the growth of mold and mildew under normal conditions.

### SEVEN YEAR WARRANTY AGAINST MANUFACTURING DEFECTS

See only information and printed on manufacturer's label for warranty.

### FIRE HAZARD CLASSIFICATION RESULTS

- TESTED IN ACCORDANCE WITH ASTM E 84 (TUNNEL TEST)
- CLASS "0" FRI-0 (0.00) • CLASSIFICATION (0.00)
- CLASS (SINGAPORE) • (0.00)

The product is intended for use in buildings that are properly designed and constructed to resist smoke infiltration, smoke toxicity and/or carbon dioxide, at wall, ceiling and wall systems, particularly in areas, hand-drawn.

### COPYRIGHT

Copyright © 2021 Carl Robinson. All Rights Reserved.  
WALLQUEST INC., 4400 Quince Road Drive, Memphis, TN 38117 USA  
(800) 425-0255 | [carl@wallquest.com](mailto:carl@wallquest.com) | [www.wallquest.com](http://www.wallquest.com)





CARL ROBINSON

QUEENSBIDGE



## QUEENSBRIDGE

52"-54" Type II 20 oz. Contract Wallcovering



BLANCHE

CR85410



KINGDOM

CR85402



DIMGRAY

CR85400



GARNET

CR85401

PHYSICAL PROPERTIES	
Line Weight	20.0 oz. per linear yard
Backing	15.3 oz. per square yard
Weight	35.3 oz. per square yard
Width	52" - 54"

All patterns are shown as a 20" linear yard.

DESIGN INFORMATION	
Match	Random / Breakable
Repeat	Random

FEDERAL SPECIFICATIONS	
Complies with	U.S. Federal Specification (22) (W-408) for Type II materials using the procedure detailed in Federal Specification (22) (W-408) for Type II materials.
U.S. A. The wallcovering meets the Federal Test Procedure Association (FTPA) Color Fastness Test.	

**ANTIBACTERIAL FEATURES**  
This wallcovering contains bactericides and mold inhibitors to discourage the growth of mold and mildew under normal conditions.

**WARRANTY AGAINST MANUFACTURING DEFECTS**  
See only information and printed on manufacturer's label for warranty.

FIRE HAZARD CLASSIFICATION RESULTS	
• Tested in accordance with ASTM E 84 (Tunnel Test)	• Class "0" (0-0.000)
• Flame Spread (0-100)	• Smoke Density (0-1.00)

The product is intended for use in buildings that are properly designed and constructed to avoid smoke infiltration, smoke detection only for smoke detection, or wall systems and wall systems, particularly in areas, hand-drawn.

**COPYRIGHT**  
Copyright © 2021 Carl Robinson. All Rights Reserved.  
WALLCOVERING, 4400 Queen Road Drive, Memphis, TN 38117 USA  
(800) 425-0255 | [carl@wallcovering.com](mailto:carl@wallcovering.com) | [www.wallcovering.com](http://www.wallcovering.com)





CARL ROBINSON

QUEENSFERRY



## QUEENSFERRY

52"-54" Type II 20 oz. Contract Wallcovering



DOVE

CR86405



GRAY CLOUD

CR86408

PHYSICAL PROPERTIES	
Unit Weight	20.0 grams per square yard
Backing	Non-woven
Width	52"-54"

All patterns are shown as 30" down product

DESIGN INFORMATION	
Match	Seamless
Repeat	30"

**FEDERAL SPECIFICATIONS**  
Complies with U.S. Federal Specification (22) (W-438) for Type II materials using the procedure detailed in Federal Specification (22) (W-438). This wallcovering meets the Federal Test Procedure Association (FTPA) 204-Cover Test.

**ANTIBACTERIAL FEATURES**  
This wallcovering contains bactericides and mildew inhibitors to discourage the growth of mold and mildew under normal conditions.

**YEAR WARRANTY AGAINST MANUFACTURING DEFECTS**  
See only information and printed on manufacturer's label for warranty.

**FIRE HAZARD CLASSIFICATION RESULTS**

- TESTED IN ACCORDANCE WITH ASTM E 84 (TUNNEL TEST)
- CLASS "0" FRI (SMALL)
- CLASS (S) (S) (S)
- CLASS (S) (S) (S)

This product is intended for use in buildings that are properly designed and constructed to avoid smoke infiltration, smoke detection only for smoke detection, and wall systems and wall systems, particularly in areas, hand-drawn.

**COPYRIGHT**  
Copyright © 2021 Carl Robinson. All Rights Reserved.  
WALLCOVERING, 4400 Queen Road Drive, Memphis, TN 38117 USA  
(800) 425-0255 | [carl@wallcoverings.com](mailto:carl@wallcoverings.com) | [www.wallcoverings.com](http://www.wallcoverings.com)





CARL ROBINSON

QUEENSBOROUGH



CARL ROBINSON

QUEENSBOROUGH | DOVE | CR85010



## QUEENSBOROUGH

52" x 54" Type II 20 oz. Contract Wallcovering



CONCRETE

CR85008



STONE

CR85007

### PHYSICAL PROPERTIES

Leaf Weight	13.5 lbs/sq yd	180 grams per square foot
Backing	17.5 lbs per square yard	250 grams per square meter
Weight	31" x 54"	1.20 lbs. / 1.20 lbs.

All patterns are shown as 100% coverage.

### DESIGN INFORMATION

Match	Design	Design
Repeat	20"	17 1/2"

### FEDERAL SPECIFICATIONS

Complies with U.S. Federal Specification (22 CFR 161) for Type II materials using the procedure detailed in Federal Specification (22 CFR 161). The wallcovering meets the Federal Test Procedure Association (FTPA) 264-Cover Test.

### ANTIBACTERIAL FEATURES

Wallcovering contains bactericides and mold inhibitors to discourage the growth of mold and mildew under normal conditions.

### STAIN RESISTANCE AGAINST MANUFACTURING DEFECTS

Use only wallcovering and products recommended by the manufacturer.

### FIRE HAZARD CLASSIFICATION RESULTS

- TESTED IN ACCORDANCE WITH ASTM E 84 (TUNING TEST)
- CLASS "A" FIRE RATED
- CLASS "A" FIRE RATED
- CLASS "A" FIRE RATED

The product is intended for use in buildings that are properly designed and constructed to resist smoke infiltration, smoke toxicity and/or carbon dioxide.

Use only wallcovering and products recommended by the manufacturer.

Copyright © 2021 Carl Robinson. All Rights Reserved.

WALLCOVERING, INC. 4400 Queen Road Drive, Memphis, TN 38117 USA  
(866) 425-0255 | [carl@wallcovering.com](mailto:carl@wallcovering.com) | [www.wallcovering.com](http://www.wallcovering.com)