




French Scroll



Cashmere
D15529388



Cement
D15529389



Pear
D15529387



Alabaster
D15529391



Jade
D15529390



Walnut
D15529392

Type III Surface Protection in a Type II Weight

DuPont™ Tedlar™ Wallcoverings offer exceptional stain and abrasion resistance. They provide a protective barrier against almost any staining agent and most cleaning solvents including bleach, alcohols, ketones (acetone, MEK) and even strong acids and alkalis. This barrier ensures staining agents can be easily cleaned leaving an undamaged, good as new appearance that can be maintained over a long period of time. Tedlar™ Wallcoverings Type II vinyl wallcovering passes the CCC-W-408D scrubability and abrasion test for Type III wallcovering.

Proven Performance History

For over 50 years, DuPont™ Tedlar® PVF technology has been a leader in protective surface applications in markets ranging from aircraft interiors, automotive parts, and graphics overlaminates. Now, DuPont is applying this proven technology to our line of Tedlar™ Wallcoverings. Their stain resistance, ease of cleaning, and broad chemical compatibility make Tedlar™ Wallcoverings the highest-performing, most durable, and freshest looking Type II wallcoverings on the market.

Mold Resistance

The surface of Tedlar™ Wallcoverings does not provide nutrients to enable mold or bacteria growth. Tedlar™ Wallcoverings are certified to pass ASTM G21 and JIS Z 2801 by MicroStar Labs, Chicago, IL.

Fire and Smoke

Tedlar™ Wallcoverings has low flame spread and smoke development ratings, exceeding the ASTM E84 Class A rating.

Pattern Appearance and Color

All patterns are designed to simulate natural materials. Subtle variations in color, texture & shading should be anticipated as these are part of the manufacturing process and add to the richness and beauty of the product.

View our website at: www.endurewalls.com

Product Specifications

Type	Type II Wallcovering
Weight	20 oz./lin. yd.
Width	52"-54"
Finish	Tedlar® Laminate
Backing	Nonwoven
Installation	Straight Match, 18" Repeat
Standards	Meets or exceeds criteria for CCC-W-408D, ASTM F793, ASTM E84, NFPA 286, ASTM G21, JIS Z 2801