



DuPont™ Tedlar™ Wallcoverings

Mod Linen



Navy
D15532848




Brick
D15532849



Burnt Orange
D15532850




Meadow Green
D15532851



Cream
D15537088




Taupe
D15532852



Beige
D15532853



Charcoal Grey
D15532854



Thunder Grey
D15532855



Pebble Grey
D15532856



Mist Gray
D15532857

Type III Surface Protection in a Type II Weight. DuPont™ Tedlar™ Wallcoverings offer exceptional stain and abrasion resistance. They provide a protective barrier against almost any staining agent and most cleaning solvents including bleach, alcohols, ketones (acetone, MEK) and even strong acids and alkalis. This barrier ensures staining agents can be easily cleaned leaving an undamaged, good as new appearance that can be maintained over a long period of time. Tedlar™ Wallcoverings Type II vinyl wallcovering passes the CCC-W-408D scrubability and abrasion test for Type III wallcovering.

Bacteria, Mold and Mildew Resistant. The surface of Tedlar™ Wallcoverings does not provide nutrients to enable mold or bacteria growth and is certified to pass ASTM G21 and JIS Z 2801 by MicroStar Labs, Chicago, IL.

Fire and Smoke. Tedlar™ Wallcoverings has low flame spread and smoke development ratings, exceeding the ASTM E84 Class A rating.

Pattern Appearance and Color. All patterns are designed to simulate natural materials. Subtle variations in color, texture & shading should be anticipated as these are part of the manufacturing process and add to the richness and beauty of the product.

Chemical Resistant. Tedlar™ Wallcoverings hold up to Bleach, Alcohol and Alkalis cleaners so you can disinfect easily. Proven to withstand 30 years in a high traffic area of a hospital and still look new.

Hygienic. Tedlar™ Wallcoverings ability to stand up to the harshest cleaning chemicals means you have easy-to-clean walls that will assist in maintaining a hygienic environment for years to come.

Indoor Air Quality. Tedlar™ Wallcoverings are Greenguard Gold IAQ certified. It meets strict chemical emissions limits and has been tested for more than 10,000 chemicals making it perfect for all your projects, including schools and healthcare facilities with sensitive individuals.

Product Specifications

Type	Tedlar™ Wallcovering - Type II	
Weight	20 oz. / lin. yd.	620.1 g. / lin. m.
Width	52"-54"	132.08 cm. - 137.16 cm.
Length	30 lin. yd.	27.432 lin. m.
Finish	Tedlar® Film Laminate	
Backing	Nonwoven	
Installation	Reverse Hang, Random Match	
Fire Rating	Class A, Exceeds ASTM E84	
Stain Resistance	Exceeds Reagents Test CCC-W-408D	
Abrasion Resistance	Passes Type III CCC-W-408D	
Scrubability	Passes Type III CCC-W-408D	
Anti-Microbial	Passes ASTM G21, JIS Z 2801	



FIND OUT MORE AT
www.endurewalls.com