

6 3

1

4

Triad Knit

With Coordinating Plain





U.S. UNITS METRIC UNITS

Total Weight: 20.0 oz per linear yard 619 grams per linear meter 13.3 oz per square yard 451 grams per square meter

Backing: Nonwoven Nonwoven
Width: 52"- 54" 1.32m - 1.37m

All patterns stocked are in 30 linear yard bolts

PATTERN DESIGN INFORMATION

VERTICAL REPEAT: RANDOM/FREE MATCH: REVERSE HANG Random Match PLAIN DESIGN INFORMATION

VERTICAL REPEAT: RANDOM/FREE MATCH: REVERSE HANG Random Match

FEDERAL SPECIFICATIONS

Questex exceeds G.S.A Federal Specification CCC-W-408D for Type II materials using test procedures detailed in Federal Specifications CCC-T-191-B. This wallcovering passes The National Fire Protection Association NFPA286 Corner Burn Test.

FIRE HAZARD CLASSIFICATION RESULTS

- TESTED IN ACCORDANCE WITH ASTM E-84 TUNNEL TEST
- CLASS "A" FIRE RATED
- FLAME SPREAD 25
- SMOKE DEVELOPED 20
- EN13501 (B-s1,d0)

This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates.

ANTI-MICROBIAL FEATURES

Vinyl wallcoverings contain bactericides and mildew inhibitors to discourage the growth of mold and mildew under normal conditions.

5 YEAR WARRANTY AGAINST MANUFACTURING DEFECTS

Use only adhesives and primers as recommended by the manufacturer.

COPYRIGHT

Copyright © 2019 Questex, All Rights Reserved. 465 Devon Park Drive, Wayne, PA 19087 USA | contract@wallquest.com www.wallquest.com/questex - MADE IN U.S.A.



Triad Knit
With Coordinating Plain

52"- 54" Type II 20oz. Contract Wallcovering





