



## **Mod Linen**



Navv D15532848



Brick D15532849



**Burnt Orange** D15532850



Meadow Green D15532851



Cream D15537088



**Taupe** D15532852



Beige D15532853



**Charcoal Grev** D15532854



**Thunder Grev** D15532855



D15532856



**Type III Surface Protection in a Type II Weight.** DuPont™ Tedlar™ Wallcoverings offer exceptional stain and abrasion resistance. They provide a protective barrier against almost any staining agent and most cleaning solvents including bleach, alcohols, ketones (acetone, MEK) and even strong acids and alkalis. This barrier ensures staining agents can be easily cleaned leaving an undamaged, good as new appearance that can be maintained over a long period of time. Tedlar™ Wallcoverings Type II vinyl wallcovering passes the CCC-W-408D scrubbability and abrasion test for Type III wallcovering.

**Bacteria, Mold and Mildew Resistant.** The surface of Tedlar™ Wallcoverings does not provide nutrients to enable mold or bacteria growth and is certified to pass ASTM G21 and JIS Z 2801 by MicroStar Labs, Chicago, IL.

**Fire and Smoke.** Tedlar<sup>™</sup> Wallcoverings has low flame spread and smoke development ratings, exceeding the ASTM E84 Class A rating.

**Pattern Appearance and Color.** All patterns are designed to simulate natural materials. Subtle variations in color, texture & shading should be anticipated as these are part of the manufacturing process and add to the richness and beauty of the product.

**Chemical Resistant.** Tedlar™ Wallcoverings hold up to Bleach, Alcohol and Alkalis cleaners so you can disinfect easily. Proven to withstand 30 years in a high traffic area of a hospital and still look new.

**Hygienic.** Tedlar™ Wallcoverings ability to stand up to the harshest cleaning chemicals means you have easy-to-clean walls that will assist in maintaining a hygienic environment for years to come.

**Indoor Air Quality.** Material health is essential. Tedlar™ Wallcoverings has undergone rigorous testing to obtain a Health Product Declaration (HPD) contributing to healthy IAQ making it perfect for all your projects, including schools and healthcare facilities with sensitive individuals.

## **Product Specifications**

Туре	Tedlar™ Wallcovering - Type II
Weight	20 oz. / lin. yd.   620.1 g. / lin. m.
Width	52"-54"   132.08 cm 137.16 cm.
Length	30 lin. yd.   27.432 lin. m.
Finish	Tedlar® Film Laminate
Backing	Nonwoven
Installation	Reverse Hang, Random Match
Fire Rating	Class A, Exceeds ASTM E84
Stain Resistance	Exceeds Reagents Test CCC-W-408D
Abrasion Resistance	Passes Type III CCC-W-408D
Scrubbability	Passes Type III CCC-W-408D
Anti-Microbial	Passes ASTM G21, JIS Z 2801



